

PA-L19.R007



Dimensions

Length	67	± 2 mm
Width	18.5	± 1 mm
Height	22	± 1 mm

Data for Pack

Nominal voltage		3.6V	3,0V - 4.2V		
Nominal capacity		2250mAh	typical		
Used cell in pack		1pcs	Panasonic UR18650A		
Internal resistance pack		98mΩ	±20mOhm (initial)		
Max charge voltage		4,2V			
Charge current	standard	430mA	0°C < T < 45°C		
	rapid	1500mA	10°C < T < 40°C		
Discharge	standard	430mA	-20°C < T < 60°C *below 0°C with limited performance		
	max. cont.	2200mA	-20°C < T < 60°C *below 0°C with limited performance		
	max. peak	2950mA	-20°C < T < 45°C t < 1ms *below 0°C with limited performance		
Short circuit current		≥22A	Typical less than 400μs		
NTC		10kΩ	technical Data NTC		
Connector	JST	XHP-3	Pin1	GND	black
			Pin2	NTC	yellow
			Pin3	PLUS	red
Cable Length		45 mm	± 5 mm		
Weight		ca. 45g	± 5 g		
Watt-hour rating		7.8Wh	acc. to UN38.3 Certificate		

Limitations by Safety Unit (SU) @ Ta 25°C

over voltage (per cell)	cut off	4280mV	± 35mV
	release	4180mV	± 35mV
under voltage (per cell)	cut off	2300mV	± 0,100 V
	release	3V	± 0,200 V
Current Limit 1 by SU		≤2.95A	continuous *do not exceed max. cont. pack discharge current
Power consumption	active	< 12.5μA	@4.2V ±5μA
	shutdown	< 1.5μA	-0/+1μA (when Ubat < 2.25V)

Recommended Charger

1 Cell CC/CV Charger